Kunshan Seigair Intelligent Technology Co., Ltd
Plant 4, No. 66, Shunxing Road, Lujia Town, Kunshan City
Tel:0512-82627666 www.seigair.com

PRODUCT SPECIFICATIONS


MODEL NAME	VOLTS (SINGLE PHASE ONLY)	RPM		AMPS		kW		NETWEIGHT	CAPACITOR	MAX PRESSURE
		50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	kg	μF	Bar
ZW190A	220-230/50Hz	1400		1.1		0.19		3.4	5	8

SOUND LEVEL : ≤63dB（A）
NORMAL AMBIENT : 0~40°C
RELATIVE HUMIDITY : 20%~80%
ENVIRONMENT :CLEAN DUST FREE


NOTES:


1. ALL DIMENSIONS ARE FOR REFERENCE ONLY;
2. DIMENSION ARE IN MILIMITERS;
3. CLEAN OR CHANGE THE AIR FILTER'S CARTRIDGE REGULARLY IS RECOMMENDED;
4. PLEASE INSTALL THE PUMP IN A GOOD HEAT-RELEASE ENVIRONMENT FOR SAFETY CONSIDERATION;
5. THE AIR ROUTE COMPONENTS (VALVES, FIXES, CONNECTING PIPES) ARE ELECTROPHORESIS TREATED ON THE SURFACES, SO THE SURFACES CAN PASS 336-HOUR SALT-SPRAY TEST.
6. TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.

PRODUCT PERFORMANCE



PRODUCT DIMENSIONS:





MOTOR WIRING DIAGRAM

RED———CAPACITOR
RED------CAPACITOR
BLACK------LINE
BLACK------LINE



Kunshan Seigair Intelligent Technology Co., Ltd
Plant 4, No. 66, Shunxing Road, Lujia Town, Kunshan City
Tel:0512-82627666 www.seigair.com

PRODUCT SPECIFICATIONS


MODEL NAME	VOLTS (SINGLE PHASE ONLY)	RPM		AMPS		kW		NETWEIGHT	CAPACITOR	MAX PRESSURE
		50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	kg	μF	Bar
ZW280A	220-230/50Hz	1400		1.4		0.32		6.0	10	8

SOUND LEVEL : ≤65dB（A）
NORMAL AMBIENT : 0~40°C
RELATIVE HUMIDITY : 20%~80%
ENVIRONMENT :CLEAN DUST FREE


NOTES:


1. ALL DIMENSIONS ARE FOR REFERENCE ONLY;
2. DIMENSION ARE IN MILIMITERS;
3. CLEAN OR CHANGE THE AIR FILTER'S CARTRIDGE REGULARLY IS RECOMMENDED;
4. PLEASE INSTALL THE PUMP IN A GOOD HEAT-RELEASE ENVIRONMENT FOR SAFETY CONSIDERATION;
5. THE AIR ROUTE COMPONENTS (VALVES, FIXES, CONNECTING PIPES) ARE ELECTROPHORESIS TREATED ON THE SURFACES, SO THE SURFACES CAN PASS 336-HOUR SALT-SPRAY TEST.
6. TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.

PRODUCT PERFORMANCE




PRODUCT DIMENSIONS:





MOTOR WIRING DIAGRAM

RED———CAPACITOR
RED------CAPACITOR
BLACK------LINE
BLACK———LINE



Kunshan Seigair Intelligent Technology Co., Ltd
Plant 4, No. 66, Shunxing Road, Lujia Town, Kunshan City
Tel:0512-82627666 www.seigair.com

PRODUCT SPECIFICATIONS


MODEL NAME	VOLTS (SINGLE PHASE ONLY)	RPM		AMPS		kW		NETWEIGHT	CAPACITOR	MAX PRESSURE
		50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	kg	μF	Bar
ZW500A	220-230/50Hz	1400		2.8		0.55		9.2	15	8

SOUND LEVEL : ≤68dB（A）
NORMAL AMBIENT : 0~40°C
RELATIVE HUMIDITY : 20%~80%
ENVIRONMENT :CLEAN DUST FREE


NOTES:

1. ALL DIMENSIONS ARE FOR REFERENCE ONLY;
2. DIMENSION ARE IN MILIMITERS;
3. CLEAN OR CHANGE THE AIR FILTER'S CARTRIDGE REGULARLY IS RECOMMENDED;
4. PLEASE INSTALL THE PUMP IN A GOOD HEAT-RELEASE ENVIRONMENT FOR SAFETY CONSIDERATION;
5. THE AIR ROUTE COMPONENTS (VALVES, FIXES, CONNECTING PIPES) ARE ELECTROPHORESIS TREATED ON THE SURFACES, SO THE SURFACES CAN PASS 336-HOUR SALT-SPRAY TEST.
6. TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.

PRODUCT PERFORMANCE



PRODUCT DIMENSIONS:



MOTOR WIRING DIAGRAM

RED———CAPACITOR
RED------CAPACITOR
BLACK------LINE
BLACK------LINE
YELLOW------GROUNG WIRE



Kunshan Seigair Intelligent Technology Co., Ltd
Plant 4, No. 66, Shunxing Road, Lujia Town, Kunshan City
Tel:0512-82627666 www.seigair.com

PRODUCT SPECIFICATIONS


MODEL NAME	VOLTS (SINGLE PHASE ONLY)	RPM		AMPS		kW		NETWEIGHT	CAPACITOR	MAX PRESSURE
		50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	kg	μF	Bar
ZW700A	220-230/50Hz	1400		3.8		0.75		10.6	30	8

SOUND LEVEL : ≤68dB（A）
NORMAL AMBIENT : 0~40°C
RELATIVE HUMIDITY : 20%~80%
ENVIRONMENT :CLEAN DUST FREE


NOTES:

1. ALL DIMENSIONS ARE FOR REFERENCE ONLY;
2. DIMENSION ARE IN MILIMITERS;
3. CLEAN OR CHANGE THE AIR FILTER'S CARTRIDGE REGULARLY IS RECOMMENDED;
4. PLEASE INSTALL THE PUMP IN A GOOD HEAT-RELEASE ENVIRONMENT FOR SAFETY CONSIDERATION;
5. THE AIR ROUTE COMPONENTS (VALVES, FIXES, CONNECTING PIPES) ARE ELECTROPHORESIS TREATED ON THE SURFACES, SO THE SURFACES CAN PASS 336-HOUR SALT-SPRAY TEST.
6. TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.

PRODUCT PERFORMANCE




PRODUCT DIMENSIONS:



MOTOR WIRING DIAGRAM

RED———CAPACITOR
RED------CAPACITOR
BLACK------LINE
BLACK------LINE
YELLOW------GROUNG WIRE



Kunshan Seigair Intelligent Technology Co., Ltd
Plant 4, No. 66, Shunxing Road, Lujia Town, Kunshan City
Tel:0512-82627666 www.seigair.com

PRODUCT SPECIFICATIONS


MODEL NAME	VOLTS (SINGLE PHASE ONLY)	RPM		AMPS		kW		NETWEIGHT	CAPACITOR	MAX PRESSURE
		50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	kg	μF	Bar
ZW850A	220-230/50Hz	1400		3.8		0.75		10.6	30	8

SOUND LEVEL : ≤68dB（A）
NORMAL AMBIENT : 0~40°C
RELATIVE HUMIDITY : 20%~80%
ENVIRONMENT :CLEAN DUST FREE


NOTES:

1. ALL DIMENSIONS ARE FOR REFERENCE ONLY;
2. DIMENSION ARE IN MILIMITERS;
3. CLEAN OR CHANGE THE AIR FILTER'S CARTRIDGE REGULARLY IS RECOMMENDED;
4. PLEASE INSTALL THE PUMP IN A GOOD HEAT-RELEASE ENVIRONMENT FOR SAFETY CONSIDERATION;
5. THE AIR ROUTE COMPONENTS (VALVES, FIXES, CONNECTING PIPES) ARE ELECTROPHORESIS TREATED ON THE SURFACES, SO THE SURFACES CAN PASS 336-HOUR SALT-SPRAY TEST.
6. TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.

PRODUCT PERFORMANCE




PRODUCT DIMENSIONS:



MOTOR WIRING DIAGRAM

RED———CAPACITOR
RED------CAPACITOR
BLACK------LINE
BLACK------LINE
YELLOW------GROUNG WIRE



Kunshan Seigair Intelligent Technology Co., Ltd
Plant 4, No. 66, Shunxing Road, Lujia Town, Kunshan City
Tel:0512-82627666 www.seigair.com

PRODUCT SPECIFICATIONS


MODEL NAME	VOLTS (SINGLE PHASE ONLY)	RPM		AMPS		kW		NETWEIGHT	CAPACITOR	MAX PRESSURE
		50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	kg	μF	Bar
ZW1100A	220-230/50Hz	1400		5.8		1.10		17.2	30	8

SOUND LEVEL : ≤70dB（A）
NORMAL AMBIENT : 0~40°C
RELATIVE HUMIDITY : 20%~80%
ENVIRONMENT :CLEAN DUST FREE


NOTES:

1. ALL DIMENSIONS ARE FOR REFERENCE ONLY;
2. DIMENSION ARE IN MILIMITERS;
3. CLEAN OR CHANGE THE AIR FILTER'S CARTRIDGE REGULARLY IS RECOMMENDED;
4. PLEASE INSTALL THE PUMP IN A GOOD HEAT-RELEASE ENVIRONMENT FOR SAFETY CONSIDERATION;
5. THE AIR ROUTE COMPONENTS (VALVES, FIXES, CONNECTING PIPES) ARE ELECTROPHORESIS TREATED ON THE SURFACES, SO THE SURFACES CAN PASS 336-HOUR SALT-SPRAY TEST.
6. TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.

PRODUCT PERFORMANCE




PRODUCT DIMENSIONS:



MOTOR WIRING DIAGRAM

RED———CAPACITOR
RED------CAPACITOR
BLACK------LINE
BLACK------LINE
YELLOW------GROUNG WIRE



Kunshan Seigair Intelligent Technology Co., Ltd
Plant 4, No. 66, Shunxing Road, Lujia Town, Kunshan City
Tel:0512-82627666 www.seigair.com

PRODUCT SPECIFICATIONS


MODEL NAME	VOLTS (SINGLE PHASE ONLY)	RPM		AMPS		kW		NETWEIGHT	CAPACITOR	MAX PRESSURE
		50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	kg	μF	Bar
ZW1500A	220-230/50Hz	1400		7.0		1.50		17.4	35	8

SOUND LEVEL : ≤70dB（A）
NORMAL AMBIENT : 0~40°C
RELATIVE HUMIDITY : 20%~80%
ENVIRONMENT :CLEAN DUST FREE


NOTES:

1. ALL DIMENSIONS ARE FOR REFERENCE ONLY;
2. DIMENSION ARE IN MILIMITERS;
3. CLEAN OR CHANGE THE AIR FILTER'S CARTRIDGE REGULARLY IS RECOMMENDED;
4. PLEASE INSTALL THE PUMP IN A GOOD HEAT-RELEASE ENVIRONMENT FOR SAFETY CONSIDERATION;
5. THE AIR ROUTE COMPONENTS (VALVES, FIXES, CONNECTING PIPES) ARE ELECTROPHORESIS TREATED ON THE SURFACES, SO THE SURFACES CAN PASS 336-HOUR SALT-SPRAY TEST.
6. TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.

PRODUCT PERFORMANCE




PRODUCT DIMENSIONS:



MOTOR WIRING DIAGRAM

RED———CAPACITOR
RED------CAPACITOR
BLACK------LINE
BLACK------LINE
YELLOW------GROUNG WIRE



Kunshan Seigair Intelligent Technology Co., Ltd
Plant 4, No. 66, Shunxing Road, Lujia Town, Kunshan City
Tel:0512-82627666 www.seigair.com

PRODUCT SPECIFICATIONS


MODEL NAME	VOLTS (SINGLE PHASE ONLY)	RPM		AMPS		kW		NETWEIGHT	CAPACITOR	MAX VACUUM
		50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	kg	mfd.	kpa
OV140	220-230/50Hz	1400	1700	1.4	1.4	0.28	0.28	8.0	10	-92

SOUND LEVEL : ≤68dB (A)
NORMAL AMBIENT : 0~40°C
RELATIVE HUMIDITY : 20%~80%
ENVIRONMENT :CLEAN DUST FREE


NOTES:


1. ALL DIMENSIONS ARE FOR REFERENCE ONLY;
2. DIMENSION ARE IN MILIMITERS;
3. CLEAN OR CHANGE THE AIR FILTER'S CARTRIDGE REGULARLY IS RECOMMENDED;
4. PLEASE INSTALL THE PUMP IN A GOOD HEAT-RELEASE ENVIRONMENT FOR SAFETY CONSIDERATION;
5. THE AIR ROUTE COMPONENTS (VALVES, FIXES, CONNECTING PIPES) ARE ELECTROPHORESIS TREATED ON THE SURFACES, SO THE SURFACES CAN PASS 336-HOUR SALT-SPRAY TEST.
6. TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.


PRODUCT PERFORMANCE



PRODUCT DIMENSIONS:








MOTOR WIRING DIAGRAM

RED———CAPACITOR
RED------CAPACITOR
BLACK------LINE
BLACK------LINE
YELLOW------GROUNG WIRE



Kunshan Seigair Intelligent Technology Co., Ltd
Plant 4, No. 66, Shunxing Road, Lujia Town, Kunshan City
Tel:0512-82627666 www.seigair.com

PRODUCT SPECIFICATIONS


MODEL NAME	VOLTS (SINGLE PHASE ONLY)	RPM		AMPS		kW		NETWEIGHT	CAPACITOR	MAX VACUUM
		50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	kg	mfd.	kpa
OV200	220-230/50Hz	1400	1700	1.8	1.8	0.42	0.42	11.0	20	-92

SOUND LEVEL : ≤68dB（A）
NORMAL AMBIENT : 0~40°C
RELATIVE HUMIDITY : 20%~80%
ENVIRONMENT :CLEAN DUST FREE


NOTES:


1. ALL DIMENSIONS ARE FOR REFERENCE ONLY;
2. DIMENSION ARE IN MILIMITERS;
3. CLEAN OR CHANGE THE AIR FILTER'S CARTRIDGE REGULARLY IS RECOMMENDED;
4. PLEASE INSTALL THE PUMP IN A GOOD HEAT-RELEASE ENVIRONMENT FOR SAFETY CONSIDERATION;
5. THE AIR ROUTE COMPONENTS (VALVES, FIXES, CONNECTING PIPES) ARE ELECTROPHORESIS TREATED ON THE SURFACES, SO THE SURFACES CAN PASS 336-HOUR SALT-SPRAY TEST.
6. TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.


PRODUCT PERFORMANCE



PRODUCT DIMENSIONS:








MOTOR WIRING DIAGRAM

RED———CAPACITOR
RED------CAPACITOR
BLACK------LINE
BLACK------LINE
YELLOW------GROUNG WIRE



Kunshan Seigair Intelligent Technology Co., Ltd
Plant 4, No. 66, Shunxing Road, Lujia Town, Kunshan City
Tel:0512-82627666 www.seigair.com

PRODUCT SPECIFICATIONS


MODEL NAME	VOLTS (SINGLE PHASE ONLY)	RPM		AMPS		kW		NETWEIGHT	CAPACITOR	MAX PRESSURE	RATED AIRFLOW
		50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	kg	μF	kPa	@200kpa
DL280A	220-230/50Hz	/		1.4		0.32		6.0	10	250	68


NOTES:


1. ALL DIMENSIONS ARE FOR REFERENCE ONLY;
2. DIMENSION ARE IN MILIMITERS;
3. CLEAN OR CHANGE THE AIR FILTER'S CARTRIDGE REGULARLY IS RECOMMENDED;
4. PLEASE INSTALL THE PUMP IN A GOOD HEAT-RELEASE ENVIRONMENT FOR SAFETY CONSIDERATION;
5. TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.

SOUND LEVEL : ≤63dB（A）
NORMAL AMBIENT : 0~40°C
RELATIVE HUMIDITY : 20%~80%
ENVIRONMENT :CLEAN DUST FREE

PRODUCT DIMENSIONS:







MOTOR WIRING DIAGRAM

RED———CAPACITOR
RED------CAPACITOR
BLACK------LINE
BLACK------LINE



Kunshan Seigair Intelligent Technology Co., Ltd
Plant 4, No. 66, Shunxing Road, Lujia Town, Kunshan City
Tel:0512-82627666 www.seigair.com

PRODUCT SPECIFICATIONS


MODEL NAME	VOLTS (SINGLE PHASE ONLY)	RPM		AMPS		kW		NETWEIGHT	CAPACITOR	MAX PRESSURE	RATED AIRFLOW
		50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	kg	μF	kPa	@200kpa
DL500A	220-230/50Hz	/		2.4		0.5		9.1	15	250	90

NOTES:

1. ALL DIMENSIONS ARE FOR REFERENCE ONLY;
2. DIMENSION ARE IN MILIMITERS;
3. CLEAN OR CHANGE THE AIR FILTER'S CARTRIDGE REGULARLY IS RECOMMENDED;
4. PLEASE INSTALL THE PUMP IN A GOOD HEAT-RELEASE ENVIRONMENT FOR SAFETY CONSIDERATION;
5. TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.


SOUND LEVEL : ≤65dB（A）
NORMAL AMBIENT : 0~40°C
RELATIVE HUMIDITY : 20%~80%
ENVIRONMENT :CLEAN DUST FREE

PRODUCT DIMENSIONS:



MOTOR WIRING DIAGRAM

RED———CAPACITOR
RED------CAPACITOR
BLACK------LINE
BLACK------LINE



Kunshan Seigair Intelligent Technology Co., Ltd
Plant 4, No. 66, Shunxing Road, Lujia Town, Kunshan City
Tel:0512-82627666 www.seigair.com

PRODUCT SPECIFICATIONS


MODEL NAME	VOLTS (SINGLE PHASE ONLY)	RPM		AMPS		kW		NETWEIGHT	CAPACITOR	MAX PRESSURE	RATED AIRFLOW
		50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	kg	μF	kPa	@200kpa
DL600A	220-230/50Hz	/		3.4		0.65		10.4	15	250	110


NOTES:

1. ALL DIMENSIONS ARE FOR REFERENCE ONLY;
2. DIMENSION ARE IN MILIMITERS;
3. CLEAN OR CHANGE THE AIR FILTER'S CARTRIDGE REGULARLY IS RECOMMENDED;
4. PLEASE INSTALL THE PUMP IN A GOOD HEAT-RELEASE ENVIRONMENT FOR SAFETY CONSIDERATION;
5. TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.

SOUND LEVEL : ≤65dB（A）
NORMAL AMBIENT : 0~40°C
RELATIVE HUMIDITY : 20%~80%
ENVIRONMENT :CLEAN DUST FREE


PRODUCT DIMENSIONS:





MOTOR WIRING DIAGRAM

RED———CAPACITOR
RED------CAPACITOR
BLACK------LINE
BLACK------LINE



Kunshan Seigair Intelligent Technology Co., Ltd
Plant 4, No. 66, Shunxing Road, Lujia Town, Kunshan City
Tel:0512-82627666 www.seigair.com

PRODUCT SPECIFICATIONS


MODEL NAME	VOLTS (SINGLE PHASE ONLY)	RPM		AMPS		kW		NETWEIGHT	CAPACITOR	MAX PRESSURE	RATED AIRFLOW
		50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	kg	μF	kPa	@200kpa
DL800A	220-230/50Hz	/		3.8		0.81		10.4	20	250	160

NOTES:

1. ALL DIMENSIONS ARE FOR REFERENCE ONLY;
2. DIMENSION ARE IN MILIMITERS;
3. CLEAN OR CHANGE THE AIR FILTER'S CARTRIDGE REGULARLY IS RECOMMENDED;
4. PLEASE INSTALL THE PUMP IN A GOOD HEAT-RELEASE ENVIRONMENT FOR SAFETY CONSIDERATION;
5. TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.

SOUND LEVEL : ≤68dB（A）
NORMAL AMBIENT : 0~40°C
RELATIVE HUMIDITY : 20%~80%
ENVIRONMENT :CLEAN DUST FREE

PRODUCT DIMENSIONS:



MOTOR WIRING DIAGRAM

RED———CAPACITOR
RED------CAPACITOR
BLACK------LINE
BLACK------LINE

